

Cover sheet for the safety data sheet

Product identification:

Trade name	PVC ADHESIVE
Intended use	Adhesive
UFI	EYMJ-MD5S-G00U-ANXF
Item number	SOR140691

Supplier submitting the safety data sheet:

Supplier:	TELL's Power AG Bahnhofweg 2 + 4 CH-6405 Immensee
-----------	---

Phone:	041 850 77 44
--------	---------------

E-Mail :	info@tellspower.ch
----------	--

National emergency number: 145 (available 24 hours, Tox Info Suisse, Zurich; for calls from Switzerland, information in German, French and Italian)

Information for users concerning:

Section 1	For commercial users only
------------------	---------------------------

Section 13	Do not dispose of completely empty packaging together with household waste. Packaging must be sent for recycling. Treat product residues and non-emptied packaging as hazardous waste. Residues may pose an explosion hazard. Do not perforate uncleaned containers, cut or weld uncleaned containers. Dispose of hazardous waste in accordance with Directive 91/689/EEC at an authorized disposal site, indicating a waste code number in accordance with Decision 2000/532/EC. Disposal should be carried out in accordance with regional, national and local laws and regulations. Local regulations may be stricter than regional or national requirements and must be observed. Switzerland: Dispose of completely empty packaging with municipal waste. Return partially emptied containers to the point of sale or hand them over to a collection point for special waste.
-------------------	--

Section 15	This product may only be supplied to professional users
-------------------	---

CATALYSEUR NAUTICOLLE - RP140691N



SAFETY DATA SHEET
(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : CATALYSEUR NAUTICOLLE
Product code : RP140691N.

1.2. Relevant identified uses of the substance or mixture and uses advised against
catalyst

1.3. Details of the supplier of the safety data sheet

Registered company name : SOROMAP PEINTURES VERNIS.
Address : 1, RUE MAURICE MALLET Z.I. DE BELIGON.17300.ROCHEFORT SUR MER.FRANCE.
Telephone : 05.46.88.36.10. Fax : 05.46.88.36.15.
contact@soromap.com
www.soromap.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 2 (Flam. Liq. 2, H225).
Eye irritation, Category 2 (Eye Irrit. 2, H319).
Respiratory sensitisation, Category 1 (Resp. Sens. 1, H334).
Skin sensitisation, Category 1 (Skin Sens. 1, H317).
Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).
This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02



GHS07



GHS08

Signal Word :

DANGER

Product identifiers :

EC 205-500-4	ETHYL ACETATE
CAS 53317-61-6	POLYISOCYANATE
CAS 9017-01-0	TOLYLENE DIISOCYANATE, PRODUCT OF OLIGOMERIZATION
CAS 26006-20-2	AROMATIC POLYISOCYANATE
EC 223-810-8	4-ISOCYANATOSULPHONYLTOLUENE
EC 247-722-4	M-TOLYLIDENE DIISOCYANATE

CATALYSEUR NAUTICOLLE - RP140691N

Additional labeling :

EUH204 Contains isocyanates. May produce an allergic reaction.

Hazard statements :

H225 Highly flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H336 May cause drowsiness or dizziness.

Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements - Prevention :

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response :

P302 + P352 IF ON SKIN: Wash with plenty of water/...

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Precautionary statements - Storage :

P403 + P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Composition :**

Identification	(EC) 1272/2008	Note	%
CAS: 141-78-6 EC: 205-500-4 REACH: 01-2119475103-46 ETHYL ACETATE	GHS07, GHS02 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]	50 \leq x % < 100
CAS: 53317-61-6 POLYISOCYANATE	GHS07 Wng Skin Sens. 1, H317 Eye Irrit. 2, H319		10 \leq x % < 25
CAS: 9017-01-0 TOLYLENE DIISOCYANATE, PRODUCT OF OLIGOMERIZATION	GHS07 Wng Skin Sens. 1, H317		2.5 \leq x % < 10
CAS: 26006-20-2 AROMATIC POLYISOCYANATE	GHS07 Wng Skin Sens. 1, H317 Eye Irrit. 2, H319		2.5 \leq x % < 10
CAS: 4083-64-1 EC: 223-810-8 REACH: 01-2119980050-47 4-ISOCYANATOSULPHONYLTOLUENE	GHS07, GHS08 Dgr Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 STOT SE 3, H335 EUH:014		0 \leq x % < 2.5

CATALYSEUR NAUTICOLLE - RP140691N

CAS: 26471-62-5 EC: 247-722-4 M-TOLYLIDENE DIISOCYANATE	GHS06, GHS08 Dgr Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 2, H330 Resp. Sens. 1, H334 STOT SE 3, H335 Carc. 2, H351 Aquatic Chronic 3, H412	[1] [2]	0 <= x % < 2.5
---	--	------------	----------------

(Full text of H-phrases: see section 16)

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures**In the event of exposure by inhalation :**

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of an allergic reaction, seek medical attention.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist

CATALYSEUR NAUTICOLLE - RP140691N

- water with AFFF (Aqueous Film Forming Foam) additive
- Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

Contaminated areas must be cleaned very quickly.

A possible decontaminant for flammable products may be : (expressed by volume) water (45 parts), ethanol or isopropanol (50 parts), concentrated ammonia (d-0.880) (5 parts). For non-flammable products: sodium carbonate (5 parts), water (95 parts).

This residue must be stored for disposal in compliance with current regulations (see section 13).

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of asthma, allergies and/or chronic or periodical breathing difficulties should not, under any circumstances, use these mixtures.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

CATALYSEUR NAUTICOLLE - RP140691N

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged : always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically non-conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid skin and eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

Suitable packaging materials :

N/A

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limits :**

- European Union (2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m3	VME-ppm	VLE-mg/m3	VLE-ppm	Notes
141-78-6	734	200	1468	400	-

- Germany - AGW (BAuA - TRGS 900, 29/01/2018) :

CAS	VME :	VME :	Excess	Notes
141-78-6		200 ppm 730 mg/m ³		2(I)

- France (INRS - ED984 :2016) :

CAS	VME-ppm	VME-mg/m3	VLE-ppm	VLE-mg/m3	Notes	TMP No
141-78-6	400	1400	-	-	-	84
26471-62-5	0.01	0.08	0.02	0.16	AR.C3	62

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CATALYSEUR NAUTICOLLE - RP140691N

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
141-78-6	200 ppm - mg/m ³	400 ppm - mg/m ³			
26471-62-5	0.02 mg/m ³	0.07 mg/m ³	-	-	-

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

ETHYL ACETATE (CAS: 141-78-6)

Final use:Exposure method:
Potential health effects:
DNEL :Exposure method:
Potential health effects:
DNEL :**Workers.**Inhalation.
Long term systemic effects.
734 mg of substance/m³Inhalation.
Long term local effects.
734 mg of substance/m³**8.2. Exposure controls****Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- PVA (Polyvinyl alcohol)
- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

- Impervious gloves in accordance with standard EN374
- Antistatic gloves in accordance with standard EN1149

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Wear antistatic clothing made from heat resistant natural or synthetic fibres in accordance with standard EN1149.

Work clothing worn by personnel shall be laundered regularly.

CATALYSEUR NAUTICOLLE - RP140691N

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties****General information :**

Physical state : Fluid liquid.
colour : N/A

Important health, safety and environmental information

pH : Not relevant.
Boiling point/boiling range : > 35°C
Flash Point : -4.00 °C.
Explosive properties, lower explosivity limit (%) : 2.1%
Explosive properties, upper explosivity limit (%) : 11.5%
Vapour pressure (50°C) : Below 110 kPa (1.10 bar).
Density : 1.07g/cm3
Water solubility : Partially soluble.
Melting point/melting range : Not specified.
Self-ignition temperature : 461 °C.
Decomposition point/decomposition range : Not specified.
% VOC : 61.3 %

9.2. Other information

VOC (g/l) : 655.40

SECTION 10 : STABILITY AND REACTIVITY

N/A

N/A

10.1. Reactivity

Keep away from oxidising agents and strongly acidic or basic materials to avoid exothermic reactions.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

The mixture can also release hydrogen cyanide, amines and alcohols.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

10.5. Incompatible materials

No data available.

CATALYSEUR NAUTICOLLE - RP140691N

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

N/A

SECTION 11 : TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

May cause hypersensitivity of the respiratory tracts with effects taking the form of asthma, rhinitis/conjunctivitis or alveolitis.

May cause an allergic reaction by skin contact.

Based on isocyanate properties and considering the toxicological data of similar mixtures, this preparation may cause irritations and/or sensitisations of the respiratory system.

It may therefore bring about asthma, respiratory difficulties and angina pectoris.

Those susceptible may display asthmatic symptoms when exposed to atmospheres with an isocyanate concentration well below those of the VLE : exposure limits.

Repeated exposure may cause permanent respiratory problems.

11.1.1. Substances**Acute toxicity :**

M-TOLYLIDENE DIISOCYANATE (CAS: 26471-62-5)

Inhalation route (n/a) : LC50 = 0.107 mg/l
Duration of exposure : 4 h

4-ISOCYANATOSULPHONYLTOLUENE (CAS: 4083-64-1)

Oral route : LD50 = 2234 mg/kg
Species : Rat

ETHYL ACETATE (CAS: 141-78-6)

Oral route : LD50 = 4935 mg/kg
Species : Rabbit

Inhalation route (n/a) : LC50 = 1600 mg/l
Species : Rat
Duration of exposure : 4 h

11.1.2. Mixture

N/A

N/A

N/A

N/A

N/A

Respiratory or skin sensitisation :

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Contains isocyanates. May cause an allergic reaction.

CATALYSEUR NAUTICOLLE - RP140691N

Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 26471-62-5 : IARC Group 2B : The agent is possibly carcinogenic to humans.

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

12.3.2. Mixtures

N/A

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :

WGK 1 : Slightly hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2017 - IMDG 2016 - ICAO/IATA 2017).

14.1. UN number

1173

14.2. UN proper shipping name

UN1173=ETHYL ACETATE

14.3. Transport hazard class(es)

- Classification :



3

14.4. Packing group

II

CATALYSEUR NAUTICOLLE - RP140691N

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	II	3	33	1 L	-	E2	2	D/E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	3	-	II	1 L	F-E,S-D	-	E2

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	3	-	II	353	5 L	364	60 L	-	E2
	3	-	II	Y341	1 L	-	-	-	E2

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2018/1480 (ATP 13)

- Container information:

The mixture is contained in packaging that does not exceed 125 ml.

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

- Particular provisions :

No data available.

- German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :

WGK 1 : Slightly hazardous for water.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer .
H412	Harmful to aquatic life with long lasting effects.
EUH014	Reacts violently with water.

CATALYSEUR NAUTICOLLE - RP140691N

Abbreviations :

DNEL : Derived No-Effect Level

CMR: Carcinogenic, mutagenic or reprotoxic.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

GHS08 : Health hazard

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.