

# Cover sheet for the safety data sheet

---

## Product identification:

Trade name	X
Intended use	X
UFI	X
Item number	X

---

## Supplier submitting the safety data sheet:

Supplier: TELL's Power AG  
Bahnhofweg 2 + 4  
CH-6405 Immensee

Phone: 041 850 77 44

E-Mail : [info@tellspower.ch](mailto:info@tellspower.ch)

**National emergency number: 145** (available 24 hours, Tox Info Suisse, Zurich;  
for calls from Switzerland, information in  
German, French and Italian)

---

## Information for users concerning:

**Section 1** For commercial users only

**Section 13** Do not dispose of completely empty packaging together with household waste. Packaging must be sent for recycling. Treat product residues and non-emptied packaging as hazardous waste. Residues may pose an explosion hazard. Do not perforate uncleaned containers, cut or weld uncleaned containers. Dispose of hazardous waste in accordance with Directive 91/689/EEC at an authorized disposal site, indicating a waste code number in accordance with Decision 2000/532/EC. Disposal should be carried out in accordance with regional, national and local laws and regulations. Local regulations may be stricter than regional or national requirements and must be observed. Switzerland: Dispose of completely empty packaging with municipal waste. Return partially emptied containers to the point of sale or hand them over to a collection point for special waste.

**Section 15** This product may only be supplied to professional users

---

safety data sheet  
 according to 1907/2006/EG, article 31

Print date: 02/10/2022

Version number 8 (replaces version 7)

revised on: 02/10/2022

## SECTION 1: Identification of the substance or mixture and the company

### 1.1 Product identifier

Trade name: Epifanes Seapower Super Poly Boat Wax UFI: UWA0-V03G-4007-PCUH 1.2 Relevant identified uses of the substance or mixture and

#### Uses advised against

- Sector of use
  - SU22 Commercial uses: Public sector (administration, education, entertainment, services, crafts)
- Product Category PC31 Polishes and Wax Blends
- Procedure category
  - PROC10 Application by roller or brush
  - PROC0 Cotton cloth or sponge
- Environmental Release Category
  - ERC10a Widespread use of low release articles (outside)
- Application of the substance / the mixture See our technical data sheet for the application of this product. waxes
- 1.3 Details of the supplier of the safety data sheet - Manufacturer/Supplier: W.Heeren & Zoon bv.

PO box 166 1430

AD Aalsmeer

Netherlands

phone +31 297-360366

email: [info@epifanes.nl](mailto:info@epifanes.nl) - Informing

department: Research & Development.

#### 1.4 Emergency number:

The Poison Centers; Telephone emergency call and information: information center against poisoning; Tel.: +49 (0) 228 19240 (emergency)

Tel.: +49 (0) 228-287 33480 (Secretariat)

Fax: +49 (0) 228 287-33278 Email:

[info@giftzentrale-bonn.de](mailto:info@giftzentrale-bonn.de) [www.ukbonn.de](http://www.ukbonn.de)  
 Center for Pediatrics Clinic and Polyclinic for  
 General Paediatrics University Hospital Bonn  
 Adenauerallee 119 53113 Bonn

## SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture -  
 Classification according to Regulation (EC) No. 1272/2008



GHS02 flame

Flam. Liquid 3

H226 Flammable liquid and vapour.

(continued on page 2)

safety data sheet  
 according to 1907/2006/EG, article 31

Print date: 02/10/2022

Version number 8 (replaces version 7)

revised on: 02/10/2022

Trade name: Epifanes Seapower Super Poly Boat Wax

(continued from page 1)



GHS08 health hazard

STOT RE 2

H373 May cause damage to the central nervous system with prolonged exposure or repeated exposure.



GHS05 Corrosion

Eye Dam. 1

H318 Causes serious eye damage.



GHS07

skin irritation 2

H315 Causes skin irritation.

STOT SE 3

H336 May cause drowsiness and dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects  
Effect.

- 2.2 Label elements
- Labeling according to Regulation (EC) No. 1272/2008  
The product is classified and labeled according to the CLP regulation.
- Hazard pictograms



GHS02 GHS05 GHS07 GHS08

- Signal word Danger

Hazard-determining components of labelling:  
metakaolin

alkanes, C12-14 iso

Siloxanes and Silicones, di-Me, $[[[3-[(2\text{-aminoethyl})\text{amino}]\text{propyl}]\text{dimethoxysilyl}]\text{oxy}]\text{-terminated}$ 

Stoddard Solvent

- Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H336 May cause drowsiness and dizziness.

H373 May cause damage to the central nervous system through prolonged or repeated exposure exposure.

H412 Harmful to aquatic life with long lasting effects.

- Safety instructions

P102

Keep out of the reach of children.

P210

Keep away from heat, hot surfaces, sparks, open flames and keep away from other sources of ignition. Do not smoke.

P260

Do not breathe dust/fume/gas/mist/vapours/spray.

(continued on page 3)

safety data sheet  
according to 1907/2006/EG, article 31

Print date: 02/10/2022

Version number 8 (replaces version 7)

revised on: 02/10/2022

Trade name: Epifanes Seapower Super Poly Boat Wax

(continued from page 2)

P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards · Results of PBT  
and vPvB assessment · PBT: Not applicable.

· vPvB: Not applicable.

· Determination of endocrine disrupting properties

541-02-6 2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxanes

list II

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Description:

Mixture of substances listed below with harmless additions.

· Hazardous ingredients:

CAS: 68551-19-9 EINECS: 271-369-5 Reg.nr.: 01-2119491311-45-0000	alkanes, C12-14-iso- STOT RE 2, H373; Asp. Tox. 1, H304	10-25%
CAS: 64742-47-8 EINECS: 265-149-8 Index number: 649-422-00-2 Reg.nr.: 01-2119457736-27	Distillates (petroleum), hydrotreated light flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	10-25%
CAS: 112-58-3 EINECS: 203-987-8	Hexyl Ether Skin Irrit. 2, H315; eye irritation 2, H319; STOT SE 3, H335	2.5-10%
CAS: 8052-41-3 EINECS: 232-489-3 Index number: 649-345-00-4	Stoddard Solvent Flam. Liq. 3, H226 STOT RE 1, H372; Asp. Tox. 1, H304	2.5-10%
CAS: 66402-68-4 EINECS: 266-340-9 Reg.nr.: 01-2119471518-31	metakaolin Eye Dam. 1, H318	3-10%
CAS: 71750-80-6 Reg.nr.: under C&L Inventory	Siloxanes and Silicones, di-Me,[[[3-[(2-aminoethyl)amino]propyl]dimethoxysilyl]oxy]-terminated Eye Dam. 1, H318 Skin Irrit. 2, H315	3-10%

(continued on page 4)

safety data sheet  
 according to 1907/2006/EG, article 31

Print date: 02/10/2022

Version number 8 (replaces version 7)

revised on: 02/10/2022

Trade name: Epifanes Seapower Super Poly Boat Wax

(continued from page 3) 2.5%

CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg. no.: 01-2119457558-25	<b>Propan-2-ol</b> Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 541-02-6 EINECS: 208-764-9	2,2,4,4,6,6,8,8,10,10- decamethylcyclopentasiloxane Skin Irrit. 2, H315; eye irritation 2, H319 Aquatic Chronic 4, H413	2.5%

## SVHC

541-02-6 2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxanes

## Additional information:

The wording of the listed risk phrases can be found in section 16.

#### SECTION 4: First aid measures

##### 4.1 Description of first aid measures General information:

Remove contaminated clothing immediately.

- After inhalation:

In case of unconsciousness place and transport in stable sideways position.

- After skin contact:

Wash off immediately with soap and water and rinse well.

Wash off immediately with water.

- After eye contact:

Rinse eyes under running water for several minutes with eyelids open and consult a doctor.

- After swallowing: Consult a doctor if symptoms persist.

- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### SECTION 5: Firefighting measures

- 5.1 Extinguishing media

- Suitable extinguishing agents:

CO<sub>2</sub>, extinguishing powder or water spray jet. Fight larger fires with water spray or alcohol-resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with a full jet
- 5.2 Special hazards arising from the substance or mixture Formation of toxic gases during heating or in case of fire.

No further relevant information available.

(continued on page 5)

safety data sheet  
 according to 1907/2006/EG, article 31

Print date: 02/10/2022

Version number 8 (replaces version 7)

revised on: 02/10/2022

Trade name: Epifanes Seapower Super Poly Boat Wax

(continued from page 4)

- 5.3 Advice for firefighters · Protective equipment:  
Put on breathing apparatus.

## SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and in emergencies applicable procedures  
Put on breathing apparatus.  
wear protective gear. Keep unprotected people away.
- 6.2 Environmental protection measures:  
Prevent entry into sewers, pits and basements.  
Inform respective authorities when entering in waters or the sewerage.  
  
Do not allow to enter drains/surface water/ground water.
- 6.3 Methods and material for containment and cleaning up:  
Pick up with absorbent material (sand, kieselguhr, acid binder, universal binder, sawdust).  
  
Use neutralizing agent.  
Dispose of contaminated material as waste according to Section 13.  
Ensure adequate ventilation.
- 6.4 Reference to other sections  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protective equipment.  
Information on disposal, see section 13.

## SECTION 7: Handling and storage

- 7.1 Precautions for safe handling  
Ensure good ventilation/exhaustion at the workplace.  
Avoid aerosol formation.
- Information about protection against explosions and fires:  
Keep ignition sources away - do not smoke.  
Take precautionary measures against electrostatic charging.  
Keep breathing apparatus ready.
- 7.2 Conditions for safe storage, including any incompatibilities · Storage: · Requirements to be met by storerooms and containers: No special requirements.  
  
· Information about storage in one common storage facility: Not required.  
· Further information about storage conditions: Keep container tightly closed.
- Classification according to the Ordinance on Industrial Safety and Health (BetrSichV):  
Flammable liquids · 7.3 Specific end use(s).  
No further relevant information available.

EN

(continued on page 6)

safety data sheet  
 according to 1907/2006/EG, article 31

Print date: 02/10/2022

Version number 8 (replaces version 7)

revised on: 02/10/2022

Trade name: Epifanes Seapower Super Poly Boat Wax

(continued from page 5)

### SECTION 8: Exposure controls/personal protective equipment

#### 8.1 Parameters to monitor

<b>Components with workplace-related limit values that require monitoring: 64742-47-8 Distillates (petroleum), hydrotreated light OEL See No. 2.9, AGS, Y 67-63-0 propan-2-ol OEL long-term value: 500 mg/m<sup>3</sup>, 200 ml/m<sup>3</sup></b>		
	2(II); DFG, Y	
64742-47-8 Distillates (petroleum), hydrotreated light OEL Comp. No. 2.9, AGS, Y 67-63-0 propan-2-ol OEL long-term value: 500 mg/m <sup>3</sup> , 200 ml/m <sup>3</sup>		
	2(II); DFG, Y	

Legal regulations AGW: TRGS 900

<b>DNEL (Derived No Effect Level) for professionals</b>		
<b>112-58-3 hexyl ether</b>		
dermal	Long-term - local effects. Long term - systemic effects.	0.554 µg/cm <sup>2</sup> (employee) 1,666 mg/kg/day (employee)
Inhalative	Long term - systemic effects.	117 mg/m <sup>3</sup> (employees)
<b>8052-41-3 Stoddard Solvent</b>		
dermal	Long-term - local effects. Acute - systemic effects. Long term - systemic effects.	7.56 µg/cm <sup>2</sup> (employee) 30 mg/kg lg/day (employee) 80 mg/kg/day (employee)
Inhalation	Long term - local effects. Acute - systemic effects. Long term - systemic effects.	44 mg/m <sup>3</sup> (employee) 55 mg/m <sup>3</sup> (employee) 44 mg/m <sup>3</sup> (employee)
<b>67-63-0 propan-2-ol</b>		
dermal	Long term - systemic effects.	888 mg/kg/day (industry)
Inhalative	Long-term - systemic effects.	500 mg/m <sup>3</sup> (industry)
<b>541-02-6 2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane</b>		
	Inhalative Long term - local effects. 24.2 mg/m <sup>3</sup> (employees) 97.3 mg/m <sup>3</sup> (employees) Long term - systemic effects.	

(continued on page 7)



safety data sheet

according to 1907/2006/EG, article 31

Print date: 02/10/2022

Version number 8 (replaces version 7)

revised on: 02/10/2022

Trade name: Epifanes Seapower Super Poly Boat Wax

(continued from page 6)

## - DNEL (Derived No Effect Level) for general audiences

## 112-58-3 hexyl ether

Orally	Long-term systemic effects.	4 mg/kg bw/day (General Population)
dermal	Long-term - systemic effects. 100 mg/kg bw/day	(General Population)
	Long-term - local effects.	0.554 mg/m <sup>3</sup> (General Population)
Inhalation	Long term - systemic effects. 34.8 mg/m <sup>3</sup> (General Population)	

## 8052-41-3 Stoddard Solvent

Orally	Acute - systemic effects Long-term systemic effects.	50 mg/kg (general population) 10.56 mg/kg bw/day (General Population)
dermal	Acute - systemic effects.	60 mg/kg bw/day (General Population)
	Long-term - systemic effects. 40 mg/kg bw/day	(General Population)
	Long-term - local effects.	3.78 mg/m <sup>3</sup> (General Population)
Inhalation	Acute - local effects.	55 mg/cm <sup>2</sup> (General Population)
	Acute - systemic effects.	55 mg/m <sup>3</sup> (general population)
	Long-term - systemic effects. 22 mg/m <sup>3</sup> (general population)	
	Long-term - local effects. 22 mg/m <sup>3</sup> (general population)	

## 67-63-0 propan-2-ol

Orally	Long-term systemic effects.	26 mg/kg bw/day (General Population)
dermal	Long-term - systemic effects. 319 mg/kg bw/day	(General Population)
Inhalation	Long term - systemic effects. 89 mg/m <sup>3</sup> (general population)	

## 541-02-6 2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxanes

Oral	Long-term systemic effects.	5 mg/kg bw/day (General Population)
dermal	Long-term - local effects.	4.3 mg/m <sup>3</sup> (General Population)
Inhalation	Long term - systemic effects. 17.3 mg/m <sup>3</sup> (General Population)	

## - PNEC values

## 112-58-3 hexyl ether

aquatic compartment.	0.136 µg/l (salt water)
	1.36 µg/l (fresh water)
STP floor	100 mg/l (Segmentation, Targeting and Positioning)
	0.533 mg/kg (fresh water)

(continued on page 8)



safety data sheet  
 according to 1907/2006/EG, article 31

Print date: 02/10/2022

Version number 8 (replaces version 7)

revised on: 02/10/2022

Trade name: Epifanes Seapower Super Poly Boat Wax

(continued from page 7)

floor	0.106 mg/kg (soil)
sediment	0.053 mg/kg (salt water)
<b>8052-41-3 Stoddard Solvent</b>	
Aquarium compartment. 0.14 mg/l (fresh water)	
Aquarium compartment. 0.35 mg/l (salt water)	
STP positioning)	1.14 mg/l (segmentation, targeting and
floor	1.14 mg/kg (freshwater)
sediment	0.14 mg/kg (salt water)
<b>67-63-0 propan-2-ol</b>	
Sewage	2,251 mg/l (sewage treatment plant)
treatment plant aquarium compartment. 140.9 mg/l (fresh water)	
Aquarium compartment. 140.9 mg/l (salt water)	
floor	552 mg/kg (freshwater)
Intermittently	140.9 mg/L (Intermittent)
floor	28 mg/kg (soil)
sediment	552 mg/kg (salt water)
<b>541-02-6 2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxanes</b>	
aquatic compartment. 0.12 µg/l (salt water)	
STP	1.2 µg/l (fresh water)
floor	10 mg/l (Segmentation, Targeting and Positioning)
floor	11 mg/kg (freshwater)
sediment	2.54 mg/kg (soil)
sediment	1.1 mg/kg (salt water)

**Components with biological limit values:**

67-63-0 propan-2-ol

BLV 25 mg/l

Test material: whole blood  
 Time of sampling: end of exposure or end of shift  
 Parameters: acetone

25 mg/l

Test material: urine  
 Time of sampling: end of exposure or end of shift  
 Parameters: acetone

**- Additional information:**

The lists valid at the time of creation served as the basis.

- 8.2 Limitation and monitoring of exposure
- Appropriate engineering controls  
No further information, see section 7.
- Individual protective measures, for example personal protective equipment
- General protection and hygiene measures:  
Keep away from food, drink and animal feedingstuffs.  
Take off dirty, soaked clothes immediately.  
Wash hands before breaks and at the end of work.

(continued on page 9)

safety data sheet  
 according to 1907/2006/EG, article 31

Print date: 02/10/2022

Version number 8 (replaces version 7)

revised on: 02/10/2022

Trade name: Epifanes Seapower Super Poly Boat Wax

(continued from page 8)

Separate storage of protective clothing.

Avoid skin contact.

Avoid contact with eyes and skin.

- Respiratory protection Not required.
- Handguard



protective gloves

The glove material has to be impermeable and resistant to the product/  
 Substance / the preparation.

Due to a lack of tests, no recommendation for the glove material can be made for the  
 product / the preparation / the chemical mixture.

Selection of the glove material taking the breakthrough times into account,  
 permeation rates and degradation.

- Material of gloves

The selection of a suitable glove is not only based on the material, but  
 also depends on other quality features and from manufacturer to manufacturer  
 different. Because the product is a preparation of several substances  
 represents, the durability of glove materials is not  
 predictable and must therefore be checked before use.

- Penetration time of glove material

The exact breakthrough time can be found out from the protective glove manufacturer and  
 to comply with

- For continuous contact of a maximum of 15 minutes, gloves are made of the following

Materials suitable:

butyl rubber

- Eye/face protection



Tight fitting goggles

## SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

Physical state - Color -

Odour: - Odor threshold:

- Melting point/freezing

point: - Boiling point or

initial boiling point and

Boiling range -

Flammability - Lower

and upper explosion limits

Lower:

Upper:

Flash point:

Fluid

According to the product description

Characteristic

Not determined.

Not determined.

82°C

Not applicable.

0.8 vol%

6 vol%

41°C

(continued on page 10)

safety data sheet  
**according to 1907/2006/EG, article 31**

Print date: 02/10/2022

Version number 8 (replaces version 7)

revised on: 02/10/2022

Trade name: Epifanes Seapower Super Poly Boat Wax

(continued from page 9)

<b>Ignition temperature:</b>	425°C
Decomposition temperature: pH value:	Not determined.
	Not determined.
Viscosity:	
- Kinematic viscosity at 20 °C	100s (ISO 6mm)
Dynamic:	Not determined.
- Solubility	
- Water:	Not or only slightly miscible.
partition coefficient n-octanol/ water (log value)	Not determined.
Vapor pressure at 20 °C:	5.4 hPa
- Density and/or specific gravity	
- Density at 20 °C:	1.009 g/cc
- Relativ density	Not determined.
- <b>Vapor Density</b>	Not determined.

- 9.2 Other information	
- Look:	
- Shape:	Fluid
- Important health and safety information environmental protection and safety	
- <b>Ignition temperature</b>	The product is not self-igniting.
- Explosive properties:	The product is not explosive, however, is the Formation of explosive vapours/ Air mixtures possible.
solvent content:	
- Organic solvents:	7.2%
- VOCs	7.20%
	<b>VOC:</b>
	72.6g/L / 0.61lb/gal
- State change	
- Evaporation rate	Not determined.

- Details of physical hazard classes	
- Explosive substances/mixtures and <b>Products containing explosives are not applicable</b>	
- There are no flammable gases	
- No aerosols	
- No oxidizing gases	
- No gases under pressure	
- Flammable liquids Flammable liquid and vapour.	
- Flammable solids not applicable	
- Self-reactive substances and mixtures are not applicable	
- Pyrophoric liquids · Pyrophoric solids ·	omitted
Self-heating substances and	omitted
mixtures	omitted
- Substances and mixtures in contact develop flammable gases with water not applicable	

(continued on page 11)

safety data sheet

according to 1907/2006/EG, article 31

Print date: 02/10/2022

Version number 8 (replaces version 7)

revised on: 02/10/2022

Trade name: Epifanes Seapower Super Poly Boat Wax

(continued from page 10)

• Oxidizing liquids	omitted
• Oxidizing solids	omitted
• Organic peroxides	omitted
• Corrosive to metals substances and mixtures	omitted
• Desensitized substances/mixtures and products containing explosives	omitted

**SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:  
No decomposition if used as directed.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid  
No further relevant information available.
- 10.5 Incompatible materials:  
No further relevant information available.
- 10.6 Hazardous decomposition products:  
No dangerous decomposition products known.

**SECTION 11: Toxicological information**

- 11.1 Information on the hazard classes in accordance with Regulation (EC) No. 1272/2008
- Acute toxicity

Based on the available data, the classification criteria are not met.

## Classification-relevant LD/LC50 values:

68551-19-9 alkanes, C12-14-iso		
Orally	LD50	>5 mg/l (rat)
dermal	LD50	>2,000 mg/kg bw (rabbit)
Inhalative LC50		>5.3 mg/l (rat)
112-58-3 hexyl ether		
Orally	LD50	30,900 mg/kg bw (rat)
dermal	LD50	6,900 mg/kg bw (rabbit)
67-63-0 propan-2-ol		
Orally	LD50	5,045 mg/kg bw (rat)
dermal	LD50	12,800 mg/kg bw (rabbit)
	Long-term exposure (8 hours TWA): 50ppm	650 mg/m <sup>3</sup> (workplace exposure limits)
Inhalative LC50/4 h		30 mg/l (rat)

- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitization  
Based on the available data, the classification criteria are not met.

(continued on page 12)

Trade name: Epifanes Seapower Super Poly Boat Wax

(continued from page 11)

- Germ cell mutagenicity  
Based on the available data, the classification criteria are not met.
- Carcinogenicity  
Based on the available data, the classification criteria are not met.
- Reproductive toxicity  
Based on the available data, the classification criteria are not met.
- Specific target organ toxicity - single exposure  
May cause drowsiness and dizziness.
- Specific target organ toxicity - repeated exposure  
May cause damage to the central nervous system through prolonged or repeated exposure.
- Aspiration hazard  
Based on the available data, the classification criteria are not met.
- 11.2 Information on other hazards - Endocrine

disruptive properties 541-02-6 2,2,4,4,6,6,8,8,10,10-

decamethylcyclopentasiloxane

list II

## SECTION 12: Ecological information

- 12.1 Toxicity - Aquatic  
toxicity: No further relevant information available.
  - 12.2 Persistence and degradability  
No further relevant information available.
  - 12.3 Bioaccumulative potential  
No further relevant information available.
  - 12.4 Mobility in soil No further relevant information available.
  - 12.5 Results of PBT and vPvB assessment - PBT: Not applicable.
  - vPvB: Not applicable.
  - 12.6 Endocrine disrupting properties For information  
on endocrine disrupting properties see Section 11.
  - 12.7 Other adverse effects - Remark: Harmful  
to fish.
  - Additional ecological information: -
- General notes:**  
 Water hazard class 3 (self-assessment): highly hazardous to water Do not allow to reach ground water, water bodies or sewage system, even in small quantities.
- Must not get into the sewage or drainage ditch undiluted or unneutralized.**
- Danger to drinking water even if the smallest amounts leak into the ground. harmful to aquatic organisms**

EN

(continued on page 13)

safety data sheet  
 according to 1907/2006/EG, article 31

Print date: 02/10/2022

Version number 8 (replaces version 7)

revised on: 02/10/2022

Trade name: Epifanes Seapower Super Poly Boat Wax

(continued from page 12)

**SECTION 13: Disposal considerations**

- 13.1 Waste treatment methods
- Recommendation:  
 Must not be disposed together with household garbage. Not in the sewers let reach.

- European waste catalogue

08 00 00 WASTE	FROM MANUFACTURE, PREPARATION, DISTRIBUTION AND USE (MCVA) OF COATINGS (PAINTS, COATINGS, ENAMEL), ADHESIVES, SEALANTS AND INKS
08 01 00 wastes	from MFSU and removal of paint and varnish
08 01 11* waste	paint and varnish containing organic solvents or other contain dangerous substances
HP3	flammable
HP4	irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Hazard
HP14	ecotoxic

## Uncleaned packaging:

- Recommendation: Disposal must be made according to official regulations.

**SECTION 14: Transport information**

- 14.1 UN number or ID number

ADR, IMDG, IATA UN1993

- 14.2 UN proper shipping name

ADR 1993 FLAMMABLE LIQUID, NOW  
 IMDG FLAMMABLE LIQUID, NOS  
 IATA FLAMMABLE LIQUID, NOS (ISOPROPANOL (ISOPROPYL ALCOHOL), Distillates (petroleum), hydrotreated light)

- 14.3 Transport hazard classes

ADR



- Class 3 (F1) Flammable liquids
- Danger label 3

(continued on page 14)

safety data sheet  
 according to 1907/2006/EG, article 31

Print date: 02/10/2022

Version number 8 (replaces version 7)

revised on: 02/10/2022

Trade name: Epifanes Seapower Super Poly Boat Wax

(continued from page 13)

## IMDG, IATA



Class **3 Flammable liquids**  
 Labels **3**

· 14.4 Packing group  
 ADR, IMDG, IATA **III**

**14.5 Environmental hazards:**  
 Marine pollutants: **no**

· 14.6 Special precautions for  
 the user **Caution: Flammable liquids**  
 · Number identifying the hazard  
 (Kemler number): **30**  
 EMS number: **FE,SE \_\_\_\_\_**  
 · Stowage Category **A**

· 14.7 Bulk Carriage on the  
 Sea route according to IMO instruments **Not applicable.**

## Transport/further information:

## ADR

Exempted quantities (EQ): **E1**  
 Limited Quantity (LQ) **5L**  
 Exempted quantities (EQ) **Code: E1**  
**Maximum net quantity per inner packaging:**  
**30ml**  
**Maximum net quantity per outer packaging:**  
**1000ml**  
 · Carriage category **3**  
 · Tunnel restriction code **D/E**  
 · Remarks: **> 450L: 3 F1, III**

## IMDG

Limited quantities (LQ) **5L**  
 Excepted quantities (EQ) **Code: E1**  
**Maximum net quantity per inner**  
**packaging: 30ml**  
**Maximum net quantity per outer**  
**packaging: 1000ml**  
 · Remarks: **> 30L: 3, III**

UN "Model Regulation": **UN No. 1993, FLAMMABLE LIQUID,  
 NAG, 3, III**

EN

(continued on page 15)



safety data sheet  
 according to 1907/2006/EG, article 31

Page: 15/16

Print date: 02/10/2022

Version number 8 (replaces version 7)

revised on: 02/10/2022

Trade name: Epifanes Seapower Super Poly Boat Wax

(continued from page 14)

**SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU - Named dangerous substances - ANNEX I None of the ingredients are listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Quantity threshold (in tonnes) for use in lower tier establishments  
5,000 tons
- Quantity threshold (in tonnes) for use in upper tier establishments  
50,000 tons
- REGULATION (EC) No. 1907/2006 ANNEX XVII Conditions of restriction: 3, 70 - Directive 2011/65/EU on

the restriction of the use of certain hazardous  
 Substances in electrical and electronic equipment - Annex II

None of the ingredients are included.

REGULATION (EU) 2019/1148

Appendix I - RESTRICTED EXPLOSIVES PRECURSORS (Upper  
 Concentration limit for an Article 5(3) permit)

None of the ingredients are included.

· Appendix II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients are included.

· Regulation (EC) No. 273/2004 on drug precursors

None of the ingredients are included.

· Regulation (EC) No. 111/2005 laying down rules for the  
 Monitoring of trade in drug substitutes between the Community and third countries

None of the ingredients are included.

National regulations:

Technical Instructions Air:

class share in %	
NK	2.5-10

- Water hazard class: Water hazard class 3 (self-assessment): extremely hazardous for water.

- Other regulations, restrictions and prohibition ordinances

- Substances of very high concern (SVHC) according to REACH, Article 57 541-02-6

2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane

15.2 Chemical safety assessment:

A chemical safety assessment has not been carried out.

**SECTION 16: Other information The**

information is based on the current state of our knowledge, but it does not represent a guarantee of product properties and does not constitute a contractual legal relationship.

(continued on page 16)

safety data sheet  
 according to 1907/2006/EG, article 31

Print date: 02/10/2022

Version number 8 (replaces version 7)

revised on: 02/10/2022

Trade name: Epifanes Seapower Super Poly Boat Wax

(continued from page 15)

## - Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness and dizziness.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.

## - Department issuing data sheet: Research &amp; Development.

Contact person: JJ van Dijk, tel: +31 297 360678, email: rend@epifanes.nl Date of previous version: 09.02.2022

Version number of previous version: 7 Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labeling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

GefStoffV: Ordinance on Hazardous Substances, Germany

VOC: Volatile Organic Compounds (US, EU)

DNEL: Derived No Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal

dose, 50 percent PBT: Persistent, Bioaccumulative and

Toxic SVHC: Substances of Very High Concern vPvB: very

Persistent and very Bioaccumulative Flam. Liq. 2: Flammable

liquids - Category 2 Flam. Liq. 3: Flammable Liquids - Category 3

Skin Irrit. 2: Skin irritation/corrosion - Category 2 Eye Dam. 1: Serious eye

damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation

- Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1 STOT RE 2:

Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard

- Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic

Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 Aquatic Chronic 4: Hazardous

to the aquatic environment - long-term aquatic hazard - Category 4

## - \* Data changed compared to the previous version