

COVERAGE FOR SWITZERLAND

SECTION 1 DESIGNATION OF THE MIXTURE AND THE COMPANY

1.1 Product identifier

Product name	: Epoxy Stick
Item number	: 87004
UFI	FQXR-P728-W002-033S

1.2 Uses of the mixture

SU21 Consumer product, Boat and ship maintenance

1.3 Details about the supplier

Supplier : TELL's Power AG Bahnhofweg 2 + 4 CH-6405 Immensee

Phone : 041 850 77 44

E-Mail : <u>info@tellspower.ch</u>

Website : www.tellspower.ch

1.4 Emergency number

EMERGENCY PHONE TOX Center: **145** (24 hrs.)



According to Regulation (EU) No 453/2010

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name	:	STAR BRITE EPOXY/ALUMINUM PUTTY STICK
Product code	:	87004

1.2. Relevant identified uses of the substance or mixture and uses advised against

Application : SU21 Consumer product. PC9b Fillers, putties, plasters, modelling clay.

1.3. Details of the supplier of the safety data sheet

Supplier	:	Star Brite Europe Inc.
		86 bis route de Brignais
		69630 Chaponost, France
Telephone	:	+33-478-56-77-80
Fax	:	+33-472-39-97-96
E-mail	:	jp.kitzinger@starbrite-europe.com
Website	:	www.starbrite.com

1.4. Emergency telephone number

EMERGENCY TELE	EPHONE NUMBER, for DOCTORS/FIRE BRIGADE/POLICE only:			
Telephone	: 144, 118, 117			
EMERGENCY TELEPHONE NUMBER (for DOCTORS only):				

National Poisons Information Service	145	(24/7)

SECTION 2 HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP classification (1272/2008/EC)	:	Skin irritation, category 2. Eye irritation, category 2. Skin sensitization, category 1. Hazardous to the aquatic environment — Chronic category 3.
Human health hazards Physical/chemical hazards Environmental hazards	:	Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Not classified as dangerous according to statutory EC-Directives. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements (1272/2008/EC): Hazard pictograms :



Signal word	: Warning	
H- and P-phrases	: H317 H412 P101 P102 P280 gloves P333+P313 P302+P352 P362+P364 P501	May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Wear protective gloves. If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN: Wash with plenty of water/soap. Take off contaminated clothing and wash it before reuse. Dispose of contents/container to an official chemical waste depot.



Additional labelling (for all packaging sizes)

: Contains: reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700); 2,4,6-tris(dimethylaminomethyl)phenol.

2.3. Other hazards

Other information

: The product does not need to carry all label elements required by Article 17 of Regulation (EC) No 1272/2008 on the basis of Annex I, point 1.5.2.1. Exemption for packages where the contents do not exceed 125 ml. Does not contain PBT or vPvB substances in concentrations higher than 0,1%.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.2. Mixtures

Product description : Mixture.

Information on hazardous substances:

Substance name	Concentration (w/w) (%)	CAS nr.	EC number	Remark	REACH nr.
Talc	50 - 75	14807-96-6	238-877-9	MAC	
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	5 - < 25	25068-38-6	500-033-5		
aluminium powder (stabilised)	1 - < 5	7429-90-5	231-072-3		
2,4,6-tris(dimethylaminomethyl)phenol	1 - < 5	90-72-2	202-013-9		

Substance name	Hazard Class	H-phrases	Pictograms	
Talc				
reaction product: bisphenol-A-	Eye Irrit. 2; Skin Irrit. 2;	H319; H315; H317;	GHS07; GHS09	H319 : C >= 5 %
(epichlorhydrin); epoxy resin (number	Skin Sens. 1; Aquatic	H411		H315 : C >= 5 %
	Chronic 2			
aluminium powder (stabilised)	Water-react. 2; Flam. Sol. 1	H261; H228	GHS02	
	Acute Tox. 4; Eye	H302; H319; H315; H312; H317; H412	GHS07	

Occupational exposure limit(s), if relevant, are listed in section 8.

Reference is made to chapter 16 for full text of each relevant H phrase.

SECTION 4 FIRST-AID MEASURES

4.1. Description of first aid measures

First aid measures	
Inhalation	: Not applicable.
Skin contact	: Take off contaminated clothing. Wash off skin with plenty of water and soap before product dries up. Consult a doctor if irritation occurs.
Eye contact Ingestion	 Wash out with (lukewarm) water for at least 15 minutes. Remove contact lenses. Consult a doctor. Do not induce vomiting. Do rinse the mouth. Give one glass of water. Never give anything by mouth to an unconscious person. Consult a doctor if victim feels unwell.

4.2. Most important symptoms and effects, both acute and delayed

Effects and symptoms		
Inhalation	: No specific effects and/or symptoms are known.	
Skin contact	: Irritant. May cause redness and irritation, sensitisation. May produce an allergic reaction.	

Product name	: Star brite Epoxy/Aluminum Putty Stick			Page 2/10
Date of issue	: 18-05-2016	Replaces issue dated	:	INFO CARE SDS



According to Regulation (EU) No 453/2010

Eye contact	: 1	Irritant. May cause redness and pain.
Ingestion	: 1	May cause a feeling of sickness, vomiting and diarrhoea.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5 FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media	
Suitable	: Carbondioxide (CO2). Foam. Dry chemical. Water fog.
Not suitable	: Water jet.

5.2. Special hazards arising from the substance or mixture

Special exposure hazards	:	None known.
Hazardous thermal	:	Carbon monoxide may be evolved if incomplete combustion occurs.
decomposition products		

5.3. Advice for firefighters

Special protective	:	Use adequate respiratory equipment in case of insufficient ventilation.
equipment for fire-fighters		

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions : Danger of slipping. Clean up spills immediately. Wear shoes with non-slip soles. Avoid contact with spilled or released material.

6.2. Environmental precautions

Environmental precautions	:	Avoid release of product into sewers, surface water and/or ground water. Waste product should not
		be allowed to contaminate soil or water.
Other information	:	Notify authorities if any exposure to the general public or the environment occurs or is likely to
		OCCUF.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Collect spilled material in containers. Dispose at an authorised waste collection point. Wash away remainder with plenty of water and soap.

6.4. Reference to other sections

Reference to other sections : See also section 8.

SECTION 7 HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling

: Handle in accordance with good occupational hygiene and safety practices in well-ventilated areas. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage	:	Keep in a cool, dry and well-ventilated place (< 35 °C).
Recommended packaging	:	Keep only in the original container.

· ___



Non recommended : None known. packaging

7.3. Specific end use(s)

Use

: Use only as directed.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure : Occupational exposure limits have not been established for this product. Derived no-effect levels (DNEL) have not been established for this product. Predicted no-effect concentrations (PNEC) have not been established for this product.

Workplace exposure limits (mg/m³):

Chemical name	,		STEL 15 min (mg/m3)	Comments
Talc	GB	1	-	Respirable fraction.
Talc		2	-	
aluminium powder (stabilised)		2		

Derived no-effect level (DNEL) for workers:

Chemical name	Route of	DNEL, short-term		DNEL, long-term	
	exposure				
	-	Local effect	Systemic effect	Local effect	Systemic effect
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	Dermal		8,33 mg/kg bw		8,33 mg/kg bw/day
aluminium powder (stabilised)	Inhalation Inhalation		12,25 mg/m3		12,25 mg/m3 3,72 mg/m3

Derived no-effect level (DNEL) for consumers:

Chemical name	Route of	DNEL, short-term		DNEL, long-term	
	exposure				
		Local effect	Systemic effect	Local effect	Systemic effect
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	Dermal				3,571 mg/kg bw/day
aluminium powder (stabilised)	Oral Oral		0,75 mg/kg bw		0,75 mg/kg bw/day 3,95 mg/kg bw/day

Predicted no-effect concentration (PNEC):

Chemical name	Route of exposure	Fresh water	Marine water	
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	Water	0,006 mg/l	0,001 mg/l	
	Sediment Intermittent water STP Soil Oral	0,996 mg/kg	0,1 mg/kg	0,018 mg/l 10 mg/l 0,196 mg/kg 11 mg/kg food
aluminium powder (stabilised)	Water STP	0,074 mg/l		20 mg/l

8.2. Exposure controls

Engineering measures Hygienic measures : Comply with standard precautionary measures for working with chemicals.

: When using do not eat, drink or smoke.



Personal protective equipment:

The efficiency of personal protective equipment depends among other things on temperature and degree of ventilation. Always get professional advice for the particular local situation.



•

Body protection	: Wear appropriate protective clothing, overalls or suit, and similar boots in accordance with EN
	365/367 resp. 345. Suitable material: not known. Indication of permeation breakthrough time: not
	known.
Respiratory protection	: Take care of sufficient ventilation.
Hand protection	: Wear appropriate safety gloves in accordance with EN 374. Suitable material: laminated film. ± 0,5
	mm. Indication of permeation breakthrough time: not known.
Eye protection	: Wear appropriate safety glasses with side shields, in accordance with EN 166, when there is
	danger of possible eye contact.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

	, ,	
Appearance	: Solid.	
Colour	: Grey.	
Odour	: Characteristic.	
Odour threshold	: Not known.	
рН	: Not applicable.	Solid.
Solubility in water	: Not soluble.	
Partition coefficient (n-	: Not known.	
octanol/water)		
Flash point	: Not relevant.	Solid.
Flammability (solid, gas)	: Not flammable.	Not easily ignitable.
Auto ignition temperature	: Not known.	Does not contain substances with a known auto ignition temperature.
Boiling point/boiling range	: Not known	
Melting point/melting range	: Not known.	
Explosive properties	: None known.	Does not contain explosives.
Explosion limits (% in air)	: Not applicable.	
Oxidising properties	: Not applicable.	Does not contain oxidizing substances.
Decomposition temperature	: > 200 °C	
Viscosity (20°C)	: Not applicable.	Solid.
Viscosity (40°C)	: Not applicable.	Almost solid at 40 °C.
Vapour pressure (20°C)	: Very low.	Solid.
Vapour density (20°C)	: Not applicable.	The solvent content of this product is less than 1%.
Relative density (20°C)	: 1,93 g/ml	
Evaporation rate	: Very low.	Solid.

SECTION 10 STABILITY AND REACTIVITY

10.1. Reactivity			
Reactivity	: See sub-sections below.		
10.2. Chemical stability			
Stability	: Stable under normal conditions.		
10.3. Possibility of hazardous reactions			
Reactivity	: No other hazardous reactions known.		

: ----



10.4. Conditions to avoid

Conditions to avoid : See section 7.

10.5. Incompatible materials

Materials to avoid : Keep away from oxidizing agents.

10.6. Hazardous decomposition products

Hazardous decomposition : Not known. products

SECTION 11 TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

No toxicological research has been carried out on this product. Inhalation

malation	
Acute toxicity	: Not applicable. No specific effects and/or symptoms are known.
Corrosion/irritation	 No specific effects and/or symptoms are known. Not classified - based on available data, the classification criteria are not met.
Sensitisation	: Does not contain substances classified as respiratory sensitiser. Not classified - based on available
Carcinogenicity	 data, the classification criteria are not met. Does not contain carcinogenic substances. Not classified - based on available data, the classification criteria are not met.
Mutagenicity	: Does not contain mutagenic substances. Not classified - based on available data, the classification criteria are not met.
Skin contact	
Acute toxicity	: Calculated LD50: > 5000 mg/kg.bw. Ingredients of unknown toxicity: < 1 %. ATE: > 2000 mg/kg.bw. Low toxicity. Not classified - based on available data, the classification criteria are not met.
Corrosion/irritation	: Irritant. May cause redness.
Sensitisation	: May cause sensitisation by skin contact. May produce an allergic reaction.
Mutagenicity	: Does not contain mutagenic substances. Not classified - based on available data, the classification criteria are not met.
Eye contact	
Corrosion/irritation	: Irritant.
Ingestion	
Acute toxicity	: Calculated LD50: > 1249 mg/kg.bw. Ingredients of unknown toxicity: < 1 %. ATE: > 2000 mg/kg.bw. Low toxicity. Not classified - based on available data, the classification criteria are not met.
Aspiration	: Not classified - based on available data, the classification criteria are not met. Does not contain substances with an aspiration hazard.
Corrosion/irritation	: May cause a feeling of sickness, vomiting and diarrhoea.
Carcinogenicity	Does not contain carcinogenic substances. Not classified - based on available data, the classification criteria are not met.
Mutagenicity	: Does not contain mutagenic substances. Not classified - based on available data, the classification criteria are not met.
Reprotoxicity	Development: Not expected to be reprotoxic. Development: Not classified - Based on available data, the classification criteria are not met. Fertility: not expected to be reprotoxic. Fertility: Not classified - based on available data, the classification criteria are not met.

Toxicological information:

Chemical name	Property		Method	Test animal
(epichlorhydrin); epoxy resin (number	Genotoxicity - in vivo	Negative		Mouse
average molecular weight ≤ 700)	Skin irritation	Slightly irritant	OECD 404	Rabbit

: ----



SAFETY DATA SHEET

According to Regulation (EU) No 453/2010

	LD50 (dermal)	> 23000 mg/kg bw		Rat
	NOEL (carcinogenicity,	100 mg/kg bw/d		Rat
	dermal)			
	Skin sensitisation	Sensitizing.		Guinea pig
	NOAEL (oral)	50 mg/kg bw/d	OECD 408	Rat
	LD50 (oral)	> 2000 mg/kg bw	OECD 420	Rat
	Eye irritation	Non-irritant	OECD 405	Rabbit
	LC50 (inhalation) -	> 5000 mg/m3		Rat
	estimate			
2,4,6-tris(dimethylaminomethyl)phenol	Skin irritation	Severely irritant		Rat
	LD50 (oral)	1200 mg/kg bw		Rat
	Eye irritation	Severely irritant		Rabbit
	LD50 (dermal)	1280 mg/kg bw		Rat

SECTION 12 ECOLOGICAL INFORMATION

12.1. Toxicity

No ecotoxicological research has been carried out on this product. Ecotoxicity : Harmful to aquatic organisms. Calcul

: Harmful to aquatic organisms. Calculated LC50 (fish): 6 mg/l. Calculated EC50 (waterflea): 6 mg/l. Contains 3 % of components with unknown hazards to the aquatic environment.

12.2. Persistence and degradability

Persistence – degradability : May cause long-term adverse effects in the aquatic environment.

12.3. Bioaccumulative potential

Bioaccumulative potential : No specific information known.

12.4. Mobility in soil

Mobility

: Little chance of penetration of spilled product into the ground and surface water.

12.5. Results of PBT and vPvB ass

PBT/vPvB assessment : Does not contain PBT or vPvB substances in concentrations higher than 0,1%.

12.6. Other adverse effects

Other information : Not applicable.

Ecological information:

Chemical name	Property		Method	Test animal
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	LC50 (fish)	> 1 mg/l	OECD 203	Oncorhynchus mykiss
	Ultimate aerobic biodegradation (%)	0 %	OECD 301 F	
	EC50 (waterflea)	> 1 mg/l	OECD 202	Daphnia magna
	NOEC (waterflea) - chronic	0,3 mg/l.d	OECD 211	Daphnia magna
	IC50 (algea)	9,4 mg/l	EPA 660/3-75-009	Scenedesmus subspicatus
2,4,6-tris(dimethylaminomethyl)phenol	LC50 (fish)	175 mg/l		Cyprinus carpio
	IC50 (algea)	84 mg/l	OECD 201	Desmodesmus subspicatus
	Ultimate aerobic biodegradation (%)	4 %	OECD 301 D	
	Log P(ow)	0,219		



According to Regulation (EU) No 453/2010

SECTION 13 DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product residues	: Do not dispose empty pack with waste produced by households. Containers may be recycled. Treat product residues and non-empty pack as hazardous waste.
Additional warning	: None.
European waste catalogue	: Dispose hazardous waste in accordance with Directive 91/689/EEC under acknowledgement of a waste code according to Commission Decision 2000/532/EC to an official chemical waste depot.
Local legislation	: Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

SECTION 14 TRANSPORT INFORMATION

14.1. UN number

UN nr. : None.

14.2. UN proper shipping name

Transport name : Not regulated.

14.3/14.4/14.5. Transport hazard class(es)/Packing group/Environmental hazards

ADR/RID/ADN (road/railwa Class	-	inland waterways) This product is not classified according to ADR/RID/ADN.
IMDG (sea) Class Marine pollutant		This product is not classified according to IMDG. No
IATA (air) Class	:	This product is not classified according to IATA.

14.6. Special precautions for user

Other information : Country specific variations may apply.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

- Marpol
- : Not intended to be carried in bulk according to International Maritime Organisation (IMO) instruments. Packaged liquids are not considered bulk.

SECTION 15 REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Community regulations	:	Regulation (EC) No 453/2010 (REACH), Regulation (EC) No 1272/2008 (CLP) and other
		regulations.

15.2. Chemical safety assessment

Chemical safety	:	Not applicable.
assessment		

SECTION 16 OTHER INFORMATION

16.1. Other information

: ----



The information in this safety data sheet is compiled in compliance with Regulation (EC) No 453/2010 dated 20 May 2010 and accurate to the best of our knowledge and experience at the date of issue specified. It is the user's obligation to use this product safely and to comply with all applicable laws and regulations concerning the use of the product. This safety data sheet complements the technical information sheets but does not replace them and offers no warranty with regard to product properties.

Users are also forewarned for any hazards involved when the product is used for other purposes than those for which it is designed.

Changed or new information with regard to the previous release is indicated with an asterisk (*).

List of abbreviations and acronyms that could be (but not necessarily are) used in this safety data sheet:

ADR	: European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	: Acute Toxicity Estimate
CLP	: Classification, Labeling & Packaging
CMR	: Carcinogenic, Mutagenic or toxic for Reproduction
EEC	: European Economic Community
IATA	: International Air Transport Association
IBC code	: International Bulk Chemical Code
IMDG	: International Maritime Dangerous Goods Code
LD50/LC50	: Lethal Dose/Concentration for 50% of a population
MAC	: Maximum Allowable Concentration
MARPOL	: International Convention for the Prevention of Pollution From Ships
NO(A)EL	: No Observed (Adverse) Effect Level
OECD	: Organisation for Economic Co-operation and Development
PBT	: Persistent, Bioaccumulative and Toxic
PC	: Chemical product category
PT	: Product type
REACH	: Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	: Regulations concerning the International Carriage of Dangerous Goods by Rail
STP	: Sewage Treatment Plant
SU	: Sector of Use
TWA/STEL	: Time-Weighted Average/Short Term Exposure Limit
UN	: United Nations
VOC	: Volatile Organic Compounds
vPvB	: Very Persistent and Very Bioaccumulative
Full text of hazard classes	mentioned in section 3
	: Flammable solid, category 1.
	: Acute toxicity, category 4.
	: Skin irritation, category 2.
Eye Irrit. 2	
	: Skin sensitization, category 1/1A/1B.
Aquatic Chronic 2	
Aquatic Chronic 3	
Water-react. 2	: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 2.
Full text of H-phrases ment	
H228	Flammable solid.
H261	In contact with water releases flammable gases.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Number format	: "," used as decimal separator.



End of safety data sheet.